




MODEL #:	WATTAGE:	VOLTAGE:	KELVIN:	SIZE:
BCL				
TECHNOLOGY:			ACCESSORIES:	
PROJECT:			NOTES:	
TYPE:			AREA:	

FEATURES

PRODUCT IMAGE

APPLICATION
Outdoor/Indoor
Sconce
Wet

LOCATION
Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT

LED CHIPS USED	TESTED	CRI	LIFE HOURS
LG/NICHIA/SAMSUNG	LM80 AND LM82	80+	50,000

LED BULB WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
6	600	450
9	900	675
12	1200	900

VOLTAGE
Standard: TD - 120V TRIAC/ELV DIMMABLE
ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
White Frosted Glass

STANDARD FINISH
Silver

MODEL #BCL ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W6 - 6 W9 - 9 W12 - 12	Standard Voltage: TD - 120V TRIAC/ELV DIMMABLE ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE	 27K  30K  35K  40K  50K	W5 - W5 1/2 H11 D5 1/2

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional)

CUSTOM FINISH OPTIONS				
 FGB Gloss Black	 FGBR Gloss Brass	 FGBZ Gloss Bronze	 FGW Gloss White	 FMB Matte Black
 FMBR Matte Brass	 FMW Matte White	 ORB Oil Rubbed Bronze		

Not seeing what you're looking for? Contact us to discuss more options.

