

MODEL #
CCL26
TECHNICAL SPECIFICATION




MODEL #:	WATTAGE:	VOLTAGE:	KELVIN:	SIZE:
TECHNOLOGY:	ACCESSORIES:			
PROJECT:	NOTES:			
TYPE:	AREA:			

FEATURES **PRODUCT IMAGE**

APPLICATION
Ceiling Indoor

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT
---------------------	---------------------	------------------	---------------------	-------------------

LED CHIPS USED LG/NICHIA/SAMSUNG
TESTED LM80 AND LM82
CRI 80+
LIFE HOURS 50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
11	1276	1008
17	1972	1557
23	2668	2107
35	4060	3207
46	5336	4215

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@asllighting.com | www.asllighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.
© Copyright © 2026 ASL Lighting Inc. All rights reserved.



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

CR Steel Construction






STANDARD LENS

Smooth White Acrylic

STANDARD FINISH

Triangular Faux Metallic / Bronze

MODEL #CCL26 ORDER FORM









WATTAGE *	VOLTAGE	KELVIN	SIZE	
W11 - 11	Standard Voltage: ND - 120V NON DIMMABLE	 27K	L49 - L49 1/4 W11 H3 1/8	
W17 - 17		 30K		
W23 - 23		DV - 120V/277V NON DIMMABLE		 35K
W35 - 35		TD - 120V TRIAC/ELV DIMMABLE		 40K
W46 - 46		DVD - 120/277V 0-10V DIMMABLE		 50K

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
BLD - Bi-Level Dimming EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional) CCS - Cable Cord Suspension System CO - Convenience Outlet FUS - Fused IB - Individually Boxed PK1 - Canopy/Pendant Kit/1 ROD PK2 - Canopy/Pendant Kit/2 RODS PK3 - Canopy/Pendant Kit/3 RODS RS - Rocker Switch

CUSTOM FINISH OPTIONS

 FGB Gloss Black	 FGBR Gloss Brass	 FGBZ Gloss Bronze	 FGW Gloss White	 FMB Matte Black
 FMBR Matte Brass	 FMW Matte White	 ORB Oil Rubbed Bronze		

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2026 ASL Lighting Inc. All rights reserved.



Approval upon request