



MODEL #:	WATTAGE:	VOLTAGE:	KELVIN:	SIZE:
CVPGA				
TECHNOLOGY:			ACCESSORIES:	
PROJECT:			NOTES:	
TYPE:			AREA:	

FEATURES

PRODUCT IMAGE



APPLICATION

120-227V Bulb Compatible

Ceiling

Outdoor



LOCATION

Wet



LIGHT PROPERTIES

Available Kelvin Options:



2700K
WARM WHITE



3000K
SOFT WHITE



3500K
NEUTRAL



4000K
COOL WHITE



5000K
DAYLIGHT

TESTED

LM80 AND LM82

CRI

80+

WATTAGE
E26 MED BASE BULB

VOLTAGE
Standard: TD - 120V TRIAC/ELV DIMMABLE
ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
 Die Cast Aluminum

STANDARD LENS
 Clear Glass

STANDARD FINISH
 Aluminum Sand Blast

MODEL #CVPGA ORDER FORM

WATTAGE	VOLTAGE	KELVIN	SIZE
WE26 MED BASE BULB - E26 MED BASE BULB	Standard Voltage: TD - 120V TRIAC/ELV DIMMABLE ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE	 27K  30K  35K  40K  50K	H9 - H9 X D4.25

Not seeing what you're looking for? Contact us to discuss more options.

