

MODEL #  
**LCM**

TECHNICAL SPECIFICATION



MODEL #:	WATTAGE:	VOLTAGE:	KELVIN:	SIZE:
TECHNOLOGY:	ACCESSORIES:			
PROJECT:	NOTES:			
TYPE:	AREA:			

FEATURES

PRODUCT IMAGE

**APPLICATION**  
Ceiling  
Outdoor

**LOCATION**  
Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT
---------------------	---------------------	------------------	---------------------	-------------------

**LED CHIPS USED**  
LG/NICHIA/SAMSUNG

**TESTED**  
LM80 AND  
LM82

**CRI**  
80+

**LIFE HOURS**  
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



**ASL LIGHTING**

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2026 ASL Lighting Inc. All rights reserved.



Approval upon request

# STANDARD OPTIONS

**STANDARD BASE CONSTRUCTION**

CR Steel Construction






**STANDARD LENS**

Smooth White Acrylic

























**STANDARD FINISH**

Brushed Nickel

MODEL # LCM ORDER FORM

WATTAGE	VOLTAGE	KELVIN	SIZE
W9 - 9	<b>Standard Voltage:</b> ND - 120V NON DIMMABLE  DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K	D9 - D9 1/4 H5
W12 - 12		 30K	
W15 - 15		 35K	
W20 - 20		 40K	
W24 - 24		 50K	
W31 - 31			

# SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY										
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control										
CUSTOM FINISH OPTIONS										
<table border="0"> <tr> <td> FGB Gloss Black</td> <td> FGBR Gloss Brass</td> <td> FGBZ Gloss Bronze</td> <td> FGW Gloss White</td> <td> FMB Matte Black</td> </tr> <tr> <td> FMBR Matte Brass</td> <td> FMW Matte White</td> <td> ORB Oil Rubbed Bronze</td> <td></td> <td></td> </tr> </table>	 FGB Gloss Black	 FGBR Gloss Brass	 FGBZ Gloss Bronze	 FGW Gloss White	 FMB Matte Black	 FMBR Matte Brass	 FMW Matte White	 ORB Oil Rubbed Bronze		
 FGB Gloss Black	 FGBR Gloss Brass	 FGBZ Gloss Bronze	 FGW Gloss White	 FMB Matte Black						
 FMBR Matte Brass	 FMW Matte White	 ORB Oil Rubbed Bronze								

*Not seeing what you're looking for? Contact us to discuss more options.*



**ASL LIGHTING**

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2026 ASL Lighting Inc. All rights reserved.



Approval upon request