

MODEL #

NB123-SN

TECHNICAL SPECIFICATION



| | | | | |
|-------------|--------------|----------|---------|-------|
| MODEL #: | WATTAGE: | VOLTAGE: | KELVIN: | SIZE: |
| TECHNOLOGY: | ACCESSORIES: | | | |
| PROJECT: | NOTES: | | | |
| TYPE: | AREA: | | | |

FEATURES

PRODUCT IMAGE

APPLICATION
Indoor
Sconce

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:



LED CHIPS USED
LG/NICHIA/SAMSUNG

TESTED
LM80 AND
LM82

CRI
80+

LIFE HOURS
50,000

| WATTAGE | SOURCE LUMENS @40K | DELIVERED LUMENS |
|---------|--------------------|------------------|
| 9 | 1259 | 1007 |
| 12 | 1520 | 1216 |
| 15 | 1750 | 1400 |
| 20 | 2494 | 1995 |
| 24 | 2793 | 2234 |
| 31 | 4000 | 3200 |

| VOLTAGE |
|-------------------------------------|
| Standard: ND - 120V NON DIMMABLE |
| DV - 120V/277V NON DIMMABLE |
| TD - 120V TRIAC/ELV DIMMABLE |
| DVD - 120/277V 0-10V DIMMABLE |



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2026 ASL Lighting Inc. All rights reserved.



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

Laser Cut Metal






STANDARD LENS

White Acrylic

STANDARD FINISH

Satin Nickel

MODEL #NB123-SN ORDER FORM

| WATTAGE * | VOLTAGE | KELVIN | SIZE |
|-----------|---|---|---------------|
| W9 - 9 | Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE |  27K | W5 - W5 H8 D4 |
| W12 - 12 | |  30K | |
| W15 - 15 | |  35K | |
| W20 - 20 | |  40K | |
| W24 - 24 | |  50K | |
| W31 - 31 | | | |

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY | ACCESSORIES |
|---|--|
| EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control | BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional) |

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2026 ASL Lighting Inc. All rights reserved.



Approval upon request